COBRA 34,000 L DIESEL BOWSER

Specifications





Manufactured on-site at our factory in Johannesburg, our 34,000 litre diesel bowsers are the fast movers in our range.

- 34,000 litre diesel tank with electronic level sensor and digital readout, effective internal baffling, and air breather
- Hydraulic motor driven diesel vane pump that delivers at ±550 l/min
- Rear bumper to house meter, filtration unit, hydraulic motor driven diesel pump unit, and dispensing hose reels
- Accurate L/C10 meter, suitable for custody transfer, with air eliminator
- Donaldson filter arrangement to handle 550l/min, with kidney filtration and water coalescing filter
- Fast Fill receiver point with Fast Fill pressureless and auto shut-off system rated to 1000l/min
- High volume hydraulic dispensing hose reel with standard 1 ¼" hose and 2" Fast Fill nozzle for dispensing at ±550l/min, alternatively at flow rates per client specification
- ✓ Low volume dispensing hose reel with standard ¾" hose and kerb side nozzle dispensing at ±120l/min, alternatively at flow rates per client specification
- Hose reels mounted in lockable cabinet
- All piping mounted in a secure, enclosed position, with no unnecessary joints or open valves, to enhance the safety factor against diesel losses
- Unit sandblasted and painted with 2-coat epoxy paint system in CAT yellow







